



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900

Technical Data Sheet

Product series **VGT215**
Product description **Green polyester tape**

General Description and Typical Applications

Heavy duty 2 mils thick polyester film coated with a high temperature fully cured silicone adhesive. The adhesive is designed to be fully stable at elevated operating temperatures. The adhesion of the silicone system allows for the tape to be die cut in small sizes offering good quick-stick. Removes cleanly leaving a well defined mask area.

Product Construction

Color(s)	Green
Total thickness	3.4 mils
Backing thickness	2.0 mils
Adhesive thickness	1.4 mils
Adhesive type	Silicone

Product Physical Characteristics

Maximum temperature	400°F
Adhesion to steel	34 oz./in. width
Tensile strength	30 lbs./in. width
Liner thickness (if applicable)	Not applicable

Storage, Shelf Life and additional information

Store under normal conditions of 70°F and 50% relative humidity out of direct sunlight.
For best performance, use this product within 12 months from date of manufacture.

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believe this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.