



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900

Technical Data Sheet

Product series **VRPT**
Product description **Red polyester plating tape**

General Description and Typical Applications

Thin and conformable for application on curved and textured surfaces. Low stretch backing for machine applications. High temperature stability and good chemical resistance. Ideal for use in various electroplating applications where full stop off masking can be achieved with the greater level of adhesive. Also used in high flying splice, circuit plating an immersion coating / anodizing. Silicone adhesive.

Product Construction

Color(s) **Red**
Total thickness **4.0 mils**
Backing thickness **1.0 mil**
Adhesive thickness **3.0 mils**
Adhesive type **Modified Silicone Adhesive**

Product Physical Characteristics

Maximum temperature **400°F**
Minimum temperature **Not available**
Adhesion to steel **30 oz./in.**
Liner thickness (if applicable) **Not applicable**

Storage, Shelf Life and additional information

Store under normal conditions of 70°F and 50% relative humidity out of direct sunlight.
For best performance, use this product within 12 months from date of manufacture.

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.