



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900

Technical Data Sheet

Product series **V9020**
Product description **PTFE Coated Glass Cloth Tape**

General Description

Substrate = Woven Fiberglass (ASTM D579)
Coating = PTFE (ASTM D4969)
Adhesive System = Silicone (ASTM D4969)
Color = Tan
Total Thickness = 0.005, 0.007, 0.008, 0.012, 0.017

Product Construction

Color(s)	Tan
Total thickness	0.005, 0.007, 0.008, 0.013, 0.017
Backing thickness	0.003, 0.005, 0.006, 0.010, 0.014
Adhesive thickness	2 mils & 3 mils (depending on thickness)
Adhesive type	Silicone or Acrylic

Product Physical Characteristics

Maximum temperature	500°F (Silicone), 350°F (Acrylic)
Minimum temperature	-100°F
Min. adhesion to steel	30 oz./in.
Tensile strength (lbs/sq. in.)	55 (3 mils), 100 (5 & 6 mils), 200 (10 mils) 320 (14 mils)
Liner thickness	Info not on file

Storage, Shelf Life and additional information

Store under normal conditions of 60° to 80°F and 40-60% relative humidity out of direct sunlight.
For best performance, use this product within 12 months from date of manufacture.

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.