



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900

Technical Data Sheet

Product series **VT468**
Product description **Double-sided banner tape**

General Description and Typical Applications

Double-faced 1 mil polyester film tape coated on both sides with a high tack and aggressive acrylic adhesive system for superior bonding. Designed as a PVC banner hem tape. Works in a wide range of temperatures and environments. Can also be used as a high temperature splicing tape. A non-stock single-sided version of this banner tape is also available.

Product Construction

Color(s)	White	
Total thickness	6.5 mils	
Backing thickness	0.5 mils	
Adhesive thickness	3.0 mils	per side
Adhesive type	Acrylic	

Product Physical Characteristics

Maximum temperature	275°F
Peel Adhesion	120 oz/in.
Tensile strength	Not available
Elongation at break	Not available
Liner thickness (if applicable)	Not available

Storage, Shelf Life and additional information

Store under normal conditions at 70°F and 50% relative humidity out of direct sunlight.
For best performance, use this product within 12 months from date of manufacture.

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.