



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900

Technical Data Sheet

Product series **VT950**
Product description **High tack yellow polyester tape**

General Description and Typical Applications

A 1 mil polyester tape with a high tack silicone adhesive. Offers excellent strength and splices on release liners and other low energy substrates. The soft, ultra high tack silicone adhesive provides quick stick. It is an excellent choice for splicing situations that demand a strong initial bond. Also good for high temperature applications.

Product Construction

Color(s) **Yellow**
Total thickness **3.5 mils**
Backing thickness **1.0 mils**
Adhesive thickness **2.5 mils**
Adhesive type **Silicone**

Product Physical Characteristics

Maximum temperature **400°F**
Minimum temperature **Not available**
Loop Tack **50 oz./in.**
Tensile strength **Not available**
Shear Test **Not available**
Liner thickness (if applicable) **N/A**

Storage, Shelf Life and additional information

Store under normal conditions at 70°F and 50% relative humidity out of direct sunlight.
For best performance, use this product within 12 months from date of manufacture.

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.